

SAMUEL HEATH


Product Data Sheet

V7168-T Trim to suit V1168-1-IS, V1168-2-IS, V1168-3-IS



V7168-TLF


Control Options



LF



LK



LL



LW




XF




XK

Dimension Key
V7101-TLF



Spares Information


V7101-T



Item	Part No.	Description
1	-	Spline Adaptor
2	-	Screw
3	-	Threaded Collar
4	-	Thread Adaptor
5	-	O-Ring
6	-	Control Handle

Item	Part No.	Description
7	-	Handle
8	-	Locking Washer
9	-	Screw
10	-	O-Ring
11	-	Indice


Installation



Note: Items A and E must be cut down to achieve the projections shown in this booklet.


1. Install the volume/diverter cartridge (A) into the valve. Secure this in place using locking nut (B).
2. Assemble the spline adaptors (C) to the volume/diverter cartridge, and secure using screw (D).
3. Assemble the thread collar (E) to the installed locking nut (B).
4. Assemble the thread adaptor (F) to the volume/diverter control body (G).
5. Screw the volume/diverter control body (G) onto the installed threaded collar (E).
6. Push the control handle (H) on to the volume/diverter control body (G) and secure using locking washer (I) and screw (J).
7. Assemble Index (K)

Adjustments




1. LF, LK, LL, XF, XK controls feature “infinite adjustment”.
2. Align handle option (A) at any desired angle.
3. Push handle option (A) on to the male taper of spindle (B).
4. Lock in to desired position using screw (C) & washer (D).

Control Assembly Instructions - LF, LK, XF & XK




1. Screw handle (A) onto spindle (B) using screw (C) and washer (D).
2. Push indice (E) into the handle option (A) to conceal the fixing.
3. The octagonal nut (F) can be rotated to the desired angle.



Note: The taper on the spindle (B) will lock in to the female taper in the handle option (A).

To remove the handle option (A) remove the screw (C) and washer (D). The handle option (A) has an M5 thread through its central fixing hole, by screwing an M5 screw in to this it will push the handle option (A) and the spindle (B) apart.


Control Assembly Instructions - LL



Step 1:

1. Secure stem (A) onto spindle (B) using screw (C) and washer (D).
2. Make note of the position of HOLE A for Step 2, align using supplied 80mm screw.

Note: the female taper in the stem (B) will lock into the female taper in the stem (A).



Step 2:

3. Push lever assembly (E) onto stem (A), ensuring HOLE A & HOLE B are in alignment.
4. Secure lever assembly (E) using screw (F) and washer (D).
5. Push indice (G) into the lever assembly (E) as shown, to conceal the fixing.

To remove the lever assembly (E), remove indice (G), screw (F) and washer (D). Lever assembly will then lift off, exposing the stem (A).



To remove the stem (A), remove screw (C) and washer (D). There is then an M5 thread through the central fixing hole on the stem (A). By screwing an M5 screw into this, it will push the stem (A) and spindle (B) apart.

Control Assembly Instructions - LW

1. Remove tapered spindle (B) and discard. This component is not required with the hand wheel (E) control option.

2. Replace taper spindle (B) with splined spindle (A) as shown.

3. Secure splined spindle (A) to the cartridge, using Screw (D) and washer (C).



Alignment:

1. Rotate hand wheel (E) to desired position.
2. Once Aligned, push hand wheel (E) onto spined spindle (A) and secure using set screw (F).

IMPORTANT NOTES

1. Installation should be carried out by a competent engineer, in accordance with water regulations.
2. Before installation ensure supply pipes are flushed clean as debris or loose particles will affect the efficiency of the ceramic disc cartridge.
3. For mixer taps it is recommended that hot & cold pressures are equally balanced.
4. To help maintain the high quality finish please clean with a soft damp cloth. Do not use abrasive polish or cleaners. Stains may be removed using diluted washing up liquid.
5. Ceramic cartridges in hard water areas. To prolong the lifespan and reduce servicing periods of your Samuel Heath tap we recommend that a suitable water softener be fitted. Consult your installer/designer for details.
6. Please note that as with all tap and shower ware it will be necessary from time to time for the products to be serviced, this should be carried out by a qualified Plumbing Engineer.

NOTES IMPORTANTES

1. L'installation doit être faite par un ingénieur qualifié, selon les règlements du Service Eau.
2. Avant l'installation, il faut s'assurer que les tuyaux d'approvisionnement sont complètement purgés. Les déchets flottants auront un effet détrimentaire sur l'efficacité de la cartouche céramique.
3. Il est recommandé que les pressions de l'eau chaude et eau froide des mitigeurs et mélangeurs soient maintenues à un niveau égal.
4. Pour conserver la finition de haute qualité, nettoyer avec un chiffon doux et humide. N'employer jamais de la cire et des produits abrasifs. Les tâches peuvent être enlevées à l'aide de liquide vaisselle pur.
5. Cartouches en céramique dans les régions à eau calcaire. Pour prolonger la durée et réduire l'entretien de votre robinetterie Samuel Heath, nous recommandons d'utiliser un adoucisseur d'eau convenable. Veuillez consulter votre installateur/fournisseur pour plus de renseignements.
6. Veuillez noter qu'un entretien sera nécessaire de temps en temps et doit être effectué par un installateur qualifié.

WICHTIGE HINWEISE

1. Installation sollte durch einen kompetenten Fachmann und nach den üblichen Vorschriften ausgeführt werden.
2. Vor Installation Wasserleitung gründlich durchspülen. Verschmutzung wird die Funktion der Kartusche erheblich einschränken.
3. Für Mischbatterien ist es wichtig, daß Wasser mit gleichem Druck eingeführt wird.
4. Um den optimalen Zustand dieses Produktes zu erhalten, wischen Sie es bitte nur mit einem feuchten, weichen Lappen ab. Auf keinen Fall Scheuermittel verwenden. Flecken lassen sich mit unverdünntem Geschirrspülmittel entfernen.
5. Keramikkartuschen in Hartwasserbereichen. Um die Lebensdauer zu verlängern und Wartungszeiten zu reduzieren empfiehlt Samuel Heath den Einsatz eines geeigneten Wasserenthärter. Fragen Sie Ihren Installateur/Designer um Rat.
6. Bitte merken Sie, dass alle Armaturen ab und zu eine Wartung brauchen. Diese soll durch einen kompetenten Installateur ausgeführt werden.

ATENCION

1. La instalación se debe realizar por un fontanero.
2. Antes de la instalación, deben pulgar las tuberías dejando correr el agua por las tuberías para que arrastren los residuos de montaje/obra, con el motivo de que no afecte la eficacia del cartucho de cerámica.
3. Para grupo baño/ducha se recomienda que las presiones del agua caliente y frío sean equilibradas.
4. Para ayudar a mantener el acabado de este producto, limpiar con un paño húmedo suave. No se debe emplear productos abrasivos de baño. Las manchas se pueden quitar empleando líquido lava-vajillas puro.
5. Cartuchos cerámicos en áreas de aguas duras. Para prolongar su vida útil y reducir los periodos de reparación de su grifo Samuel Heath recomendamos la instalación de un descalcificador de agua. Consulte a su instalador para más detalles.
6. Igual que con todo tipo de grifería y duchas, de vez en cuando será necesario llevar a cabo una revisión al producto; esto debería ser realizado por un fontanero calificado.

ATTENZIONE

1. L'impianto deve essere montato da personale tecnico in conformità alle vigenti leggi.
2. Prima dell'installazione assicurarsi che le tubature dell'acqua siano pulite. Detriti o residui di lavorazione compromettono l'efficienza del cartuccio.
3. Per i gruppi, si raccomanda che le pressioni acqua calda e acqua fredda siano ugualmente bilanciate.
4. Per mantenere la finizione di ottima qualità, pulire con un panno soffice e inumidito. Non usare creme lucidanti e materiali abrasivi. Le macchie potranno essere tolte usando del detersivo per piatti puro.
5. Come con tutti i tipi di rubinetti e docce, di volta in volta è necessario effettuare una revisione al prodotto; questo dovrebbe essere fatto da un idraulico qualificato.

SAMUEL HEATH

Head Office and Customer Service

Leopold Street
Birmingham
England
B12 0UJ

T: +44 (0)121 766 4200

Info@samuel-heath.com
www.samuel-heath.co.uk

US Customer Service
usa@samuel-heath.com
www.samuel-heath.com

8-40782
Issue: A